

Landing valves (fire valves) are used basically for attachment of hoses with branchpipes in rising mains "dry" and "wet/dry". Valves with position sensor are also installed for example as remote control for filling and emptying station according to DIN 14463 in rising mains "wet/dry".

Safety valves with air-bleeder and non-return valve are for use in drinking water main "wet" according to DIN 1988 part 6, in particular for self-help use.

- Aluminium alloys (A)
- Copper alloys (C)

Landing valves (fire valves) with 30° outlet



7000 A

Storz System Connection or thread



7000 B

Inlet thread	Outlet Storz / thread	Length (mm)	Width (mm)	Height (mm)	Weight (kg)	Ident-No.	Remarks	Alloy
G 1 A	D-Alu	110	102	60	0,500	60261693		A
G 1 A	D-MS	110	102	60	0,750	60136493		A
G 1 A	G 1 A	110	75	60	0,450	40265493		A
G 1 A	D-MS	132	120	80	0,920	60615593	⁴⁾ DIN 14461 T3	A
G 1 A	Versch. DN 19	132	140	80	0,800	60615693	⁴⁾ DIN 14461 T3	A
G 1 A	Versch. DN 25	132	140	80	0,825	60642293	⁴⁾ DIN 14461 T3	A
G 1 A	G 1 A	132	100	80	0,700	30393993	⁴⁾ DIN 14461 T3	A
G 1 ¼ A	G 1 A	140	90	80	0,750	60550693	Outlet 15°	A
G 1 ½ A	38-Alu	140	135	80	1,200	60261893		A
G 1 ½ A	38-MS	140	135	80	1,600	60261899		C
G 1 ½ A	C-Alu	140	138	98	1,300	40266093		A
G 1 ½ A	G 1 ½ A	140	110	80	1,060	40265893		A
G 2 A	45-Alu	155	130	100	1,900	60655299		C
G 2 A	C-Alu	155	160	100	1,800	60484599	DIN 14461 T3	C
G 2 A	C-MS	155	160	100	2,280	60484593	DIN 14461 T3	A

Inlet thread	Outlet Storz / thread	Length (mm)	Width (mm)	Height (mm)	Weight (kg)	Ident-No.	Remarks	Alloy
G 2 A	C-Alu	155	160	100	1,750	60558399	PN 10	C
G 2 A	C-MS	155	160	100	2,200	30275793	PN 40	A
G 2 A	45-Alu	155	130	100	1,900	60655299		C
G 2 A	C-MS	155	160	100	2,510	60573693	6)	A
G 2 A	C-Alu	155	160	100	1,920	60513399	¹⁾ DIN 14461 T3	C
G 2 A	C-MS	155	160	100	2,450	60513393	¹⁾ DIN 14461 T3	A
G 2 A	C-Alu	155	160	100	1,930	60548199	²⁾ DIN 14461 T3	C
G 2 A	C-MS	155	160	100	2,475	60548193	²⁾ DIN 14461 T3	A
G 2 A	C-Alu	155	160	100	1,945	60566299	³⁾ DIN 14461 T3	C
G 2 A	C-MS	155	160	100	2,490	60566293	³⁾ DIN 14461 T3	A
G 2 A	65-Alu	155	160	100	1,950	60404293		A
G 2 A	G 2 A	155	130	100	1,600	40223693		A
G 2 A	C-MS	155	161	100	2,650	60615793	4)	A
G 2 A	G 2 A	155	131	100	1,800	30397293	4)	A
G 2½ A	65-Alu	185	182	118	3,100	40266193		A
G 2½ A	65-MS	185	182	118	3,900	60461293		A
G 2½ A	B-Alu	185	182	128	3,100	60485799	DIN 14461 T3	C
G 2½ A	B-MS	185	182	128	3,500	60485793	DIN 14461 T3	A
G 2½ A	G 2½ A	185	152	100	2,600	40457693		A
G 2½ A	B-Alu	185	182	128	2,665	60583899	5)	C

Additional sizes and styles (also 7000 B chrome plated) on request.